



# A NEW FORCE IN CHEMICAL MANUFACTURING

Unit 2, 14-16 Lee Holm Road  
St Marys NSW 2760  
Australia

Ph: 1300 738 250 (Australia)  
Ph: +61 2 9833 9766 (International)  
Fax: 02 9623 3670

sales@chemtools.com.au  
www.chemtools.com.au

## SAFETY DATA SHEET

ISSUED OCTOBER, 2019 (VALID 5 YEARS FROM DATE OF ISSUE)

### Screen-Kleen M Stencil Cleaner

#### Section 1 - Identification of The Material and Supplier

Chemtools Pty Ltd  
Unit 2/14-16 Lee Holm Road  
St Marys NSW 2760

Phone: 1300 738 250 (business hours)  
Fax: 02 9623 3670  
www.chemtools.com.au

**Chemical nature:** Solvent blend  
**Product Name:** Screen-Kleen M Stencil Cleaner  
**Product Code:** CT-SKM  
**Product Use:** Solvent for industrial use  
**Creation Date:** October, 2019  
**Poisons Information Centre:** Phone 13 1126 from anywhere in Australia

#### Section 2 - Hazards Identification

##### Statement of Hazardous Nature

This product is classified as: Xn, Harmful. Xi, Irritating. F, Flammable. Hazardous according to the criteria of SWA. Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

**SUSMP Classification:** None allocated.

**ADG Classification:** Class 3: Flammable liquids.

**UN Number:** 1219, ISOPROPANOL (ISOPROPYL ALCOHOL)



##### GHS Signal word: DANGER

Flammable liquids Category 2

Eye irritation Category 2B

Specific Target Organ Toxicity - Single Exposure Category 3

##### HAZARD STATEMENT:

H225: Highly flammable liquid and vapour.

H320: Causes eye irritation.

H336: May cause drowsiness or dizziness.

##### PREVENTION

P210: Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

P233: Keep container tightly closed.

P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical ventilating, lighting and other equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P261: Avoid breathing fumes, mists, vapours or spray.

P262: Do not get in eyes, on skin, or on clothing.

P264: Wash contacted areas thoroughly after handling.

P271: Use only outdoors or in a well ventilated area.

#### SAFETY DATA SHEET

Issued by: Chemtools Pty Ltd

Phone: 1300 738 250 (business hours)

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)

P280: Wear protective gloves, protective clothing and eye or face protection.

**RESPONSE**

P312: Call a POISON CENTRE or doctor if you feel unwell.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice.

P381: Eliminate all ignition sources if safe to do so.

P370+P378: In case of fire, use carbon dioxide, dry chemical, foam. Alcohol resistant foam is the preferred firefighting medium but, if it is not available, fine water spray can be used.

**STORAGE**

P410: Protect from sunlight.

P402+P404: Store in a dry place. Store in a closed container.

P403+P235: Store in a well-ventilated place. Keep cool.

**DISPOSAL**

P501: If they can not be recycled, dispose of contents to an approved waste disposal plant and containers to landfill (see Section 13 of this SDS).

---

### Emergency Overview

---

**Physical Description & Colour:** Expected to be a clear colourless liquid

**Odour:** Solvent odour.

**Major Health Hazards:** Eye irritant, vapours may cause drowsiness and dizziness.

---

### Section 3 - Composition/Information on Ingredients

---

| Ingredients                | CAS No   | Conc, % | TWA (mg/m <sup>3</sup> ) | STEL (mg/m <sup>3</sup> ) |
|----------------------------|----------|---------|--------------------------|---------------------------|
| Isopropanol                | 67-63-0  | ≥90     | 983                      | 1230                      |
| 2-(2-butoxyethoxy) ethanol | 112-34-5 | ≤10     | not set                  | not set                   |

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

---

### Section 4 - First Aid Measures

---

**General Information:**

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

**Inhalation:** First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

**Skin Contact:** Wash gently and thoroughly with water (use non-abrasive soap if necessary) for 5 minutes or until chemical is removed.

**Eye Contact:** Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15 minutes or until the product is removed, while holding the eyelid(s) open. Take care not to rinse contaminated water into the unaffected eye or onto the face. Obtain medical attention immediately. Take special care if exposed person is wearing contact lenses.

**Ingestion:** If product is swallowed or gets in mouth, do NOT induce vomiting; wash mouth with water and give some water to drink. If symptoms develop, or if in doubt contact a Poisons Information Centre or a doctor.

---

### Section 5 - Fire Fighting Measures

---

**Fire and Explosion Hazards:** The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is a moderate risk of an explosion from this product if commercial quantities are involved in a fire. Firefighters should take care and appropriate precautions. Any explosion will likely spread the fire to surrounding materials. Water spray may be used to cool drums involved in a fire, reducing the chances of an explosion.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

### SAFETY DATA SHEET

**Extinguishing Media:** In case of fire, use carbon dioxide, dry chemical, foam. Alcohol resistant foam is the preferred firefighting medium but, if it is not available, fine water spray can be used. Try to contain spills, minimise spillage entering drains or water courses.

**Fire Fighting:** If a significant quantity of this product is involved in a fire, call the fire brigade. There is a danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is full fire kit and breathing apparatus.

**Flash point:** <22°C

**Upper Flammability Limit:** No data.

**Lower Flammability Limit:** No data.

**Autoignition temperature:** No data.

**Flammability Class:** Flammable Category 2 (GHS); Highly Flammable (AS1940).

## Section 6 - Accidental Release Measures

**Accidental release:** In the event of a major spill, prevent spillage from entering drains or water courses. Evacuate the spill area and deny entry to unnecessary and unprotected personnel. Wear full protective clothing including eye/face protection. All skin areas should be covered. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include Viton, Nitrile, butyl rubber, PE/EVAL and Responder. Eye/face protective equipment should comprise, as a minimum, protective glasses and, preferably, goggles. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned below (section 8).

Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Avoid using sawdust or other combustible material. Any electrical equipment should be non-sparking. Any equipment capable of building an electrostatic charge should be electrically grounded. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

## Section 7 - Handling and Storage

**Handling:** Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

**Storage:** Store in a cool, well ventilated area, and make sure that surrounding electrical devices and switches are suitable. Check containers periodically for leaks. Containers should be kept closed in order to minimise contamination and possible evaporation. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. If you keep more than 2500kg or L of Dangerous Goods of Packaging Group II, you may be required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

## Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

### SWA Exposure Limits

### TWA (mg/m<sup>3</sup>)

### STEL (mg/m<sup>3</sup>)

Isopropanol

983

1230

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

**Ventilation:** This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a fan is suggested.

**Eye Protection:** Protective glasses or goggles should be worn when this product is being used. Failure to protect your eyes may cause them harm. Emergency eye wash facilities are also recommended in an area close to where this product is being used.

## SAFETY DATA SHEET

**Skin Protection:** You should avoid contact even with mild skin irritants. Therefore you should wear suitable impervious elbow-length gloves and facial protection when handling this product for lengthy periods. See below for suitable material types.

**Protective Material Types:** We suggest that protective clothing be made from the following materials: Viton, nitrile, butyl rubber, PE/EVAL, Responder.

**Respirator:** Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above.

Eyebaths or eyewash stations should, if practical, be provided near to where this product is being handled commercially.

---

### Section 9 - Physical and Chemical Properties:

---

|   |  |
|---|--|
| <b>Physical Description &amp; colour:</b> | Expected to be a clear colourless liquid         |
| <b>Odour:</b>                             | Solvent odour.                                   |
| <b>Boiling Point:</b>                     | Not available.                                   |
| <b>Freezing/Melting Point:</b>            | No specific data. Liquid at normal temperatures. |
| <b>Volatiles:</b>                         | No data.   |
| <b>Vapour Pressure:</b>                   | No data.   |
| <b>Vapour Density:</b>                    | No data.   |
| <b>Specific Gravity:</b>                  | No data.   |
| <b>Water Solubility:</b>                  | No data.   |
| <b>pH:</b>                                | No data.   |
| <b>Volatility:</b>                        | No data.   |
| <b>Odour Threshold:</b>                   | No data.   |
| <b>Evaporation Rate:</b>                  | No data.   |
| <b>Coeff Oil/water Distribution:</b>      | No data.   |
| <b>Autoignition temp:</b>                 | No data.   |

---

### Section 10 - Stability and Reactivity

---

**Reactivity:** This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

**Conditions to Avoid:** This product should be kept in a cool place, preferably below 30°C. Keep containers tightly closed. Keep away from sources of sparks or ignition. Handle and open containers carefully. Any electrical equipment in the area of this product should be flame proofed.

**Incompatibilities:** oxidising agents.

**Fire Decomposition:** Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

**Polymerisation:** This product will not undergo polymerisation reactions.

---

### Section 11 - Toxicological Information

---

**Toxicity:** ISOPROPANOL: IMMEDIATE (ACUTE) EFFECTS:

Oral LD<sub>50</sub> (rat): 5045 mg/kg

Inhalation LC<sub>50</sub> (rat): 16,000 ppm/8 hours

Skin LD<sub>50</sub> (rabbit): 12,800 mg/kg

Skin Irritation (rabbit): 500 mg - mild

Eye Irritation (rabbit): 10 mg - moderate: 100 mg - severe

DELAYED (SUBCHRONIC AND CHRONIC) EFFECTS:

Subchronic Inhalation (rat): TC<sub>Lo</sub> 5000 ppm/6 hr/day for 90 days (intermittent) caused a change in motor activity.

Chronic Inhalation (rat): TC<sub>Lo</sub> 2500 ppm/6 hr/day for 2 years (intermittent) caused changes in liver and bladder weight and changes in urine composition.

OTHER DATA: Some very rare cases of skin hypersensitivity to Isopropanol have been reported. However, these cases do not at this time warrant Isopropanol to be classed as a sensitizer.

---

### Classification of Hazardous Ingredients

---

| Ingredient   | Risk Phrases       |
|--|--------------------|
| Isopropanol  | Conc>=20%: Xi; R36 |
| <ul style="list-style-type: none"> <li>Flammable liquid – category 2</li> <li>Eye irritation – category 2A</li> <li>Specific target organ toxicity (single exposure) – category 3</li> </ul> |                    |

### SAFETY DATA SHEET

2-(2-butoxyethoxy) Ethanol

Conc&gt;=20%: Xi; R36

- Eye irritation – category 2A

---

## Potential Health Effects

---

**Inhalation:**

**Short Term Exposure:** High vapour pressures may cause drowsiness and dizziness. In addition product is unlikely to cause any discomfort or irritation.

**Long Term Exposure:** Vapours may cause drowsiness and dizziness.

**Skin Contact:**

**Short Term Exposure:** Available data indicates that this product is not harmful. It should present no hazards in normal use. However product may be irritating, but is unlikely to cause anything more than mild transient discomfort.

**Long Term Exposure:** No data for health effects associated with long term skin exposure.

**Eye Contact:**

**Short Term Exposure:** This product is an eye irritant. Symptoms may include stinging and reddening of eyes and watering which may become copious. Other symptoms may also become evident. If exposure is brief, symptoms should disappear once exposure has ceased. However, lengthy exposure or delayed treatment may cause permanent damage.

**Long Term Exposure:** No data for health effects associated with long term eye exposure.

**Ingestion:**

**Short Term Exposure:** Significant oral exposure is considered to be unlikely. Available data shows that this product is not harmful. However, this product may be irritating to mucous membranes but is unlikely to cause anything more than transient discomfort.

**Long Term Exposure:** No data for health effects associated with long term ingestion.

**Carcinogen Status:**

**SWA:** No significant ingredient is classified as carcinogenic by SWA.

**NTP:** No significant ingredient is classified as carcinogenic by NTP.

**IARC:** Isopropanol is Class 3 - unclassifiable as to carcinogenicity to humans.

See the IARC website for further details. A web address has not been provided as addresses frequently change.

---

## Section 12 - Ecological Information

---

Insufficient data to be sure of status. The following data is for isopropanol, the main ingredient in this product.

Biodegradation: 58% theoretical BOD, 5 days at 20°C - Relatively biodegradable.

Bioconcentration: Not expected to bioaccumulate in aquatic organisms based on low octanol/water partition coefficient.

Acute Toxicity (fathead minnow): LC<sub>50</sub> 10.4 g/L /96 hr.

---

## Section 13 - Disposal Considerations

---

**Disposal:** This product may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. If neither of these options is suitable in-house, consider controlled incineration, or contact a specialist waste disposal company.

---

## Section 14 - Transport Information

---

**Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.**

**UN Number:** 1219, ISOPROPANOL (ISOPROPYL ALCOHOL)

**Hazchem Code:** •2YE

**Special Provisions:** None allocated

**Limited quantities:** ADG 7 specifies a Limited Quantity value of 1 L for this class of product.

**Dangerous Goods Class:** Class 3: Flammable liquids.

**Packing Group:** II

**Packing Instruction:** P001, IBC02

Class 3 Flammable Liquids shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 2.1 (Flammable Gases where flammable liquids and flammable gases are both in bulk), 2.3 (Toxic Gases), 4.2 (Spontaneously Combustible Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), 6 (Toxic Substances, except Flammable Liquid is nitromethane), and 7 (Radioactive Substances). They may however

## SAFETY DATA SHEET

Issued by: Chemtools Pty Ltd

Phone: 1300 738 250 (business hours)

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)

This revision issued: October, 2019

be loaded in the same vehicle or packed in the same freight container with Classes 2.1 (Flammable Gases except where the Flammable Liquids and Flammable Gases are in bulk), 2.2 (Non-Flammable Non-Toxic Gases), 4.1 (Flammable Solids), 4.3 (Dangerous When Wet Substances), 6 (Toxic Substances, where Flammable Liquid is nitromethane), 8 (Corrosive Substances), 9 (Miscellaneous Dangerous Goods), Foodstuffs or foodstuff empties.

---

### Section 15 - Regulatory Information

---

**AICS:** All of the significant ingredients in this formulation are compliant with NICNAS regulations. The following ingredient: 2-(2-butoxyethoxy) ethanol, is mentioned in the SUSMP.

---

### Section 16 - Other Information

---

**This SDS contains only safety-related information. For other data see product literature.**

**Acronyms:**

|                     |   |
|---------------------|---|
| <b>ADG Code</b>     | Australian Code for the Transport of Dangerous Goods by Road and Rail (7 <sup>th</sup> edition)                     |
| <b>AICS</b>         | Australian Inventory of Chemical Substances   |
| <b>SWA</b>          | Safe Work Australia, formerly ASCC and NOHSC  |
| <b>CAS number</b>   | Chemical Abstracts Service Registry Number  |
| <b>Hazchem Code</b> | Emergency action code of numbers and letters that provide information to emergency services especially firefighters |
| <b>IARC</b>         | International Agency for Research on Cancer   |
| <b>NOS</b>          | Not otherwise specified   |
| <b>NTP</b>          | National Toxicology Program (USA)   |
| <b>SUSMP</b>        | Standard for the Uniform Scheduling of Medicines & Poisons  |
| <b>UN Number</b>    | United Nations Number   |

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS

OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice" (Feb 2016)

### SAFETY DATA SHEET